

Safety Data Sheet

I. Product and Company Identification

PRODUCT: ISO-FLEX 609 PART A
MANUFACTURER: LymTal International, Inc.
4150 S. Lapeer Rd. Orion, MI 48359
www.lymtal.com
For Non-Emergency Questions,
Hours 8AM To 4PM Eastern Standard Time
(248) 373-8100

EMERGENCY CONTACT: 24-Hour Chemtrec (800)424-9300
Chemtrec, D.C. Area (800)483-7616

II. Hazards Identification

Classification of the Substance or Mixture:



Chronic Aquatic Environmental Hazard, CAT 2



Resp Sensitizer, CAT 1B; Aspiration Hazard, CAT 2

Signal Word: **DANGER**

Hazard Statements:

H305	May Be Harmful If Swallowed and Enters Airways	Aspiration Hazard, Cat 2
H313	May Be Harmful In Contact With Skin	Acute Toxicity, Dermal, Cat 5
H315	Causes Skin Irritation	Skin Corrosion/Irritation Cat 2
H317	May Cause An Allergic Skin Reaction	Skin Sensitizer, Cat 1
H319	Causes Serious Eye Irritation	Eye Damage/Irritation, Cat 2A
H334	May Cause Allergy Or Asthma Symptoms Or Breathing Difficulties If Inhaled	Resp Sensitizer, Cat 1A
H411	Toxic To Aquatic Life With Long Lasting Effects	Long term Aquatic environmental Hazard, Cat 2

Precautionary Statements:

P101	If Medical Advice Is Needed, Have Product Container Or Label At Hand
P102	Keep Out Of Reach Of Children
P103	Read Label Before Use
P202	Do Not Handle Until All Safety Precautions Have Been Read And Understood
P260	Do Not Breath Fume/Gas/Mist/Vapors/Spray
P261	Avoid Breathing Vapors
P264	Wash Thoroughly After Handling
P270	Do Not Eat/Drink/Smoke While Using This Product
P271	Use Only Outdoors Or In A Well Ventilated Area

P272	Contaminated Clothing Should Not Be Allowed Out Of the Workplace
P273	Avoid Release To The Environment
P280	Wear Protective Gloves/Protective Clothing/Eye Protection/Face Protection
P285	In Case Of Inadequate Ventilation Wear Respiratory Protection
P301 +P310	If Swallowed: Immediately Call A Poison Center/Doctor
P302 + P362+P353	If On Skin: take Off Contaminated Clothing, Rinse Skin With Water/Shower
P304+P340	If Inhaled: Remove Person To Fresh Air And Keep Comfortable For Breathing
P305+P351+P338	If In Eyes: Rinse Cautiously With Water For Several Minutes, Remove Contact Lenses If Present And Easy To Do. Continue Rinsing.
P308+P313	If Exposed Or Concerned: Get Medical Advice/Attention
P312	Call A Poison Center/Doctor If You Feel Unwell
P331	Do Not Induce Vomiting
P332+P313	If Skin Irritation Occurs, Get Medical Advice/Attention
P342+P311	If Experiencing Respiratory Symptoms, Call A Poison Center Or Doctor
P337+P313	If Eye Irritation Persists: Get Medical Advice/Attention
P391	Collect Spillage
P403+P235	Store In A Well Ventilated Place. Keep Cool.
P405	Store Locked Up
P501	Dispose Of Contents/Container In Accordance With Local/Regional/National/International/ Regulations

III. Composition/Information on Ingredients

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). Where a proprietary ingredient is shown, the identity may be made available as provided in this standard. All components of this product are included in the EPA Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

<u>Ingredients:</u>	<u>CAS #:</u>	<u>CONTENT</u>
Bis A Epoxy Resin	25068-38-6	0-70%
Acrylate monomer	13049-33-4	0-70%
Glycidyl ether	2238-07-5	< 2 ppm

California Proposition 65 ingredients

Phenyl Glycidyl ether	122-60-1	< 6 ppm
-----------------------	----------	---------

Section 313 Supplier Notification

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 (40CFR372)

None

IV. First Aid Measures

<u>Inhalation</u>	Remove victim from exposure. If difficulty with breathing, administer oxygen and seek medical assistance
<u>Eyes</u>	Flush eyes with cold water for a minimum of 15 minutes, lifting lower and upper eye lids throughout. Seek immediate medical attention.
<u>Skin</u>	Immediately remove contaminated clothing. Wash thoroughly with soap and water. If irritation persists seek medical attention. Wash contaminated clothing before reuse.
<u>Ingestion</u>	Do not induce vomiting, get immediate medical attention, if vomiting occurs spontaneously keep head below hips to prevent aspiration of liquids into lungs. Do not give anything by mouth to an unconscious person

V. Fire Fighting Methods

HMIS Hazard Rating No. 1

Flash Point: > 93°C (200°F)

Method: Pensky Martin C.C.

General Hazard: None.

Auto-Ignition Temp.: Not Available

Limits of Flammability

LEL: Not Available

UEL: Not Available

Extinguishing Media

For small fires, use water spray, foam, CO₂, or dry chemical. For large fires, use water spray, fog, or alcohol foam.

Special Fire & Unusual Hazards

Move containers from area if it can be done without risk. Cool fire-exposed containers with water from the side. As in any fire, wear NIOSH/MSHA approved, pressure demand self contained breathing apparatus and full protective gear.

VI. Accidental Release Measures

Action To Take For Spills/ Leaks: Avoid contact with skin or eyes. Ventilate area, eliminate all sources of ignition. Wear appropriate protective gear, contain leak or spill, salvage, clean up residue with absorbent material.

Waste Disposal Method: Handle disposal of waste material in manner that complies with local, state, province and federal regulation. Landfill if solidified, or incineration at agency approved waste-disposal facilities.

VII. Handling And Storage

Store Dry At 50-95°F. Condition Material To 65-85°F Before Using Store Away From Open Flames And High Temperatures

VIII. Exposure Controls / Personal Protection

Ventilation: Ventilation is recommended. Air movement must be designed to insure turnover at all locations in work area to avoid build up of heavy vapors.

Personal Protection Equipment: Do NOT wear contact lenses when working with this material. Use chemical goggles/safety glasses with side shields and impervious gloves. Wear clothing with long sleeves and pants. In operations where mists can be generated or the exposure limits for crystalline silica exceeded, wear a NIOSH/MSHA approved dust/fume respirator selected by a technically qualified person for the specific work conditions. Wear respirator protection whenever airborne concentrations exceed TLV ceilings or TWA, use NIOSH approved respirators for listed hazard.

Confined spaces, room, or tanks are areas where concern for TLV's is especially important. Reference OSHA regulation CFR 29 1910.134 for recommended respiratory protection.

IX. Physical And Chemical Properties

Boiling Point (°C):	N/D	Water/Oil Distribution Coefficient:	N/A
Percent Volatile:	(2 g / l)	Solubility in Water:	Negligible
Freezing Point (°C):	N/A	Specific Gravity @20° C	1.13
Vapor Pressure @ 20° C	<10	pH:	N/A
Vapor Density	>air	Evaporation Rate:	N/A
Odor Threshold:	N/A	Odor:	Slight
Appearance:	Clear liquid		
N/A = Not Available	N/D=NOT Determined	Ca. = Approximate	

X. Stability And Reactivity

HMIS Hazard Rating No. 0

Stability

Stable

Incompatibility:

Strong acids, oxidizing agents bases, amines and mercaptans.

Hazardous Decomposition Products

Oxides of Carbon; aldehydes and acids. Decomposition and Combustion products may be toxic.

Conditions To Avoid

Strong acids in bulk.

XI. Toxicity Information

HMIS Hazard Rating No. 2

PRIMARY ROUTE OF ENTRY: Inhalation, dermal, eyes

Effects Of Overexposure

Inhalation:

May cause irritation on the respiratory tract.

Eyes:

May be severely irritating to the eyes.

Skin Contact:

May be irritating to the skin. In some individuals it may cause sensitization.

Ingestion:

Not expected to be a relevant route of entry. May be slightly toxic if ingested.

Chronic:

This product does not contain chemicals considered to be carcinogenic by NTP, IARC, OSHA.

XII. Ecological Information

Marine Pollutant: NL

(NL = Not Listed; P = Moderate; PP = Severe; ND = Not Determined)

XIII. Disposal Considerations

Handle disposal of waste material in a manner that complies with all applicable local, state, provincial and federal regulations.

XIV. Transport Information

DOT SHIPPING INFORMATION

DOT Proper Shipping Name **NOT REGULATED**

DOT Hazard Class

DOT I.D Number

Label(s)

XV. Regulatory Information

OSHA Hazard Communication Standard
(29 CFR 1910.1200)

N/A

CERCLA/ Super fund (40 CFR 117,302)

N/A

SARA Extremely Hazardous Substances
(40 CFR 355)

N/A

SARA Hazard Categories (40 CFR 370)

Health : Immediate, delayed
Physical: Fire

SARA Toxic Chemicals (40 CFR 372)
Inventory Status

None
The chemicals in this product are listed on the US
TSCA Chemical Substance Inventory and the
Canadian Domestic Substances List.

XVI. Other Information

THE INFORMATION HEREIN HAS BEEN COMPILED FROM SOURCES BELIEVED TO BE RELIABLE AND IS ACCURATE TO THE BEST OF OUR KNOWLEDGE. HOWEVER, LymTal INTERNATIONAL INC. CANNOT GIVE ANY GUARANTEES REGARDING INFORMATION FROM OTHER SOURCES, AND EXPRESSLY DOES NOT MAKE ANY WARRANTIES, NOR ASSUMES ANY LIABILITY, FOR ITS USE.

Date of Preparation/ Last Revision: 8/18/2015

Safety Data Sheet

I. Product and Company Identification

PRODUCT: ISO-FLEX 609 PART B
MANUFACTURER: LymTal International, Inc.
4150 S. Lapeer Rd. Orion, MI 48359
www.lymtal.com
For Non-Emergency Questions,
Hours 8AM To 4PM Eastern Standard Time
(248) 373-8100

EMERGENCY CONTACT: 24-Hour Chemtrec (800)424-9300
Chemtrec, D.C. Area (800)483-7616

II. Hazards Identification

Classification of the Substance or Mixture:



Eye Damage/Irritation, CAT 1; Skin Corrosion/Irritation, CAT 1B



Acute Toxicity, CAT 4, Dermal; Skin Sensitizer, CAT 1;
STOT Single Exposure, CAT 3B, CNS, NE



Aspiration Hazard, CAT 2

Signal Word: **DANGER**

Hazard Statements:

H303	May Be Harmful If Swallowed	Acute Toxicity, Cat 5, Oral
H305	May Be Harmful If Swallowed and Enters Airways	Aspiration Hazard, Cat 2
H312	Harmful In Contact With Skin	Acute Toxicity, Cat 4, Dermal
H314	Causes Severe Skin Burns And Eye Damage	Skin Corrosion/Irritation, Cat 1B
H317	May Cause An Allergic Skin Reaction	Skin Sensitizer, Cat 1
H318	Causes Serious Eye Damage	Eye Damage/Irritation, Cat 1
H336	May Cause Drowsiness Or Dizziness	Stot Single Exposure, Cat 3B, CNS, NE
H412	Harmful To Aquatic Life With Long Lasting Effects	Chronic Aquatic Environmental Hazard, Cat 3

Precautionary Statements:

P102	Keep Out Of Reach Of Children
P103	Read Label Before Use
P202	Do Not Handle Until All Safety Precautions Have Been Read And Understood
P260	Do Not Breathe Dust/Fume/Gas/Mist/Vapors/Spray
P264	Wash Thoroughly After Handling
P270	Do Not Eat/Drink/Smoke While Using This Product
P271	Use Only Outdoors Or In A Well Ventilated Area
P272	Contaminated Clothing Should Not Be Allowed Out Of The Workplace
P273	Avoid Release To The Environment
P280	Wear Protective Gloves/Protective Clothing/Eye Protection/Face Protection
P284	Wear Respiratory Protection
P301+P330+P331	If Swallowed: Rinse Mouth, Do Not Induce Vomiting
P302 +P352	If On Skin: take Off Contaminated Clothing, Rinse Skin With Water/Shower
P303+P361+P353	If On Skin (Or Hair): Remove/Take Off Immediately All Contaminated Clothing. Rinse Skin With Water/Shower
P304+P340+P314	If Inhaled: Remove Person To Fresh Air And Keep Comfortable For Breathing, Get Medical Advice/Attention If You Feel Unwell.
P305+P351+P338	If In Eyes: Rinse Cautiously With Water For Several Minutes, Remove Contact Lenses If Present And Easy To Do. Continue Rinsing.
P308+P313	If Exposed Or Concerned: Get Medical Advice/Attention
P309+P311	If Exposed Or If You Feel Unwell: Call A Poison Center Or Doctor
P310	Immediately Call A Poison Center Or Doctor
P332+P313	If Skin Irritation Occurs, Get Medical Advice/Attention
P337+P313	If Eye Irritation Persists: Get Medical Advice/Attention
P363	Wash Contaminated Clothing Before Reuse
P403+P233	Store In A Well Ventilated Place. Keep Container Tightly Closed
P405	Store Locked Up
P501	Dispose Of Contents/Container In Accordance With Local/Regional/National/International/Regulations

III. Composition/Information on Ingredients

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). Where a proprietary ingredient is shown, the identity may be made available as provided in this standard. All components of this product are included in the EPA Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

<u>Ingredients:</u>	<u>CAS #:</u>	<u>CONTENT</u>
Triethylenetetramine	112-24-3	100%

State listed Components

Triethylenetetramine CA, FL, MA, NJ, PA

Section 313 Supplier Notification

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 (40CFR372)

None

IV. First Aid Measures

<u>Inhalation</u>	Remove victim from exposure. If difficulty with breathing, administer oxygen and seek medical assistance
<u>Eyes</u>	Flush eyes with cold water for a minimum of 15 minutes, lifting lower and upper eye lids throughout. Seek immediate medical attention.
<u>Skin</u>	Immediately remove contaminated clothing. Wash thoroughly with soap and water. If

Ingestion

irritation persists seek medical attention. Wash contaminated clothing before reuse. Do not induce vomiting; get immediate medical attention, if vomiting occurs spontaneously keep head below hips to prevent aspiration of liquids into lungs. Do not give anything by mouth to an unconscious person

V. Fire Fighting Methods

HMIS Hazard Rating No. 1

Flash Point: > 149°C (300°F)

Method: Pensky Martin C.C.

General Hazard: None.

Auto-Ignition Temp.: Not Available

Limits of Flammability

LEL: Not Available

UEL: Not Available

Extinguishing Media

For small fires, use water spray, foam, CO₂, or dry chemical. For large fires, use water spray, fog, or alcohol foam.

Special Fire & Unusual Hazards

Move containers from area if it can be done without risk. Cool fire-exposed containers with water from the side. As in any fire, wear NIOSH/MSHA approved, pressure demand self contained breathing apparatus and full protective gear.

VI. Accidental Release Measures

Action To Take For Spills/ Leaks: Avoid contact with skin or eyes. Ventilate the area, and eliminate all sources of ignition. Wear appropriate protective gear, contain leak or spill, salvage, and clean up residue with absorbent material.

Waste Disposal Method: Handle disposal of waste material in a manner that complies with local, state, province and federal regulation. Landfill if solidified or incineration at agency approved waste-disposal facilities.

VII. Handling And Storage

Store Dry At 50-95°F. Condition Material To 65-85°F Before Using. Store away from open flames and high temperatures

VIII. Exposure Controls / Personal Protection

Ventilation: Ventilation is recommended. Air movement must be designed to insure turnover at all locations in work area to avoid build up of heavy vapors.

Personal Protection Equipment: Do NOT wear contact lenses when working with this material. Use chemical goggles/safety glasses with side shields and impervious gloves. Wear clothing with long sleeves and pants. In operations where mists can be generated or the exposure limits for crystalline silica exceeded, wear a NIOSH/MSHA approved dust/fume respirator selected by a technically qualified person for the specific work conditions. Wear respirator protection whenever airborne concentrations exceed TLV ceilings or TWA, use NIOSH approved respirators for listed hazard.

Confined spaces, room, or tanks are areas where concern for TLV's is especially important. Reference OSHA regulation CFR 29 1910.134 for recommended respiratory protection.

IX. Physical And Chemical Properties

Boiling Point (°C):	N/D	Water/Oil Distribution Coefficient:	N/A
Percent Volatile:	2 G / L	Solubility in Water:	Negligible
Freezing Point (°C):	N/A	Specific Gravity @20° C	0.98
Vapor Pressure @ 20° C	N/A	pH:	N/A
Vapor Density	>air	Evaporation Rate:	N/A
Odor Threshold:	N/A	Odor:	Ammonical
Appearance:	Amber liquid		
N/A = Not Available	N/D=NOT Determined	Ca. = Approximate	

X. Stability And Reactivity

HMIS Hazard Rating No. 0	
<u>Stability</u>	Stable
<u>Incompatibility:</u>	Strong acids, oxidizing agents bases, amines and mercaptans.
<u>Hazardous Decomposition Products</u>	Oxides of Carbon; aldehydes and acids. Decomposition and Combustion products may be toxic.
<u>Conditions To Avoid</u>	Strong acids in bulk.

XI. Toxicity Information

HMIS Hazard Rating No. 3
PRIMARY ROUTE OF ENTRY: Inhalation, dermal, eyes
Effects Of Overexposure

<u>Inhalation:</u>	Vapors may be corrosive to the upper respiratory tract.
<u>Eyes:</u>	May cause severe damage including blindness.
<u>Skin Contact:</u>	May be irritating to the skin. In some individuals it may cause sensitization.
<u>Ingestion:</u>	Not expected to be a relevant route of entry. May cause permanent damage to the mouth throat and stomach.
Chronic:	This product does not contain chemicals considered to be carcinogenic by NTP, IARC, OSHA.

XII. Ecological Information

Marine Pollutant: NL
(NL = Not Listed; P = Moderate; PP = Severe; ND = Not Determined)

XIII. Disposal Considerations

Handle disposal of waste material in a manner that complies with all applicable local, state, provincial and federal regulations.

XIV. Transport Information

DOT SHIPPING INFORMATION

DOT Proper Shipping Name	Triethylenetetramine		
DOT Hazard Class	Class 8 (Corrosive Liquid), PG II		
DOT I.D Number	UN2259	DOT PLACARD	Corrosive

XV. Regulatory Information

OSHA Hazard Communication Standard (29 CFR 1910.1200)	N/A
CERCLA/ Super fund (40 CFR 117,302)	N/A
SARA Extremely Hazardous Substances (40 CFR 355)	N/A
SARA Hazard Categories (40 CFR 370)	Health : Immediate, delayed Physical: Fire
SARA Toxic Chemicals (40 CFR 372) Inventory Status	None The chemicals in this product are listed on the US TSCA Chemical Substance Inventory and the Canadian Domestic Substances List.

XVI. Other Information

THE INFORMATION HEREIN HAS BEEN COMPLIED FROM SOURCES BELIEVED TO BE RELIABLE AND IS ACCURATE TO THE BEST OF OUR KNOWLEDGE. HOWEVER, LymTal INTERNATIONAL INC. CANNOT GIVE ANY GUARANTEES REGARDING INFORMATION FROM OTHER SOURCES, AND EXPRESSLY DOES NOT MAKE ANY WARRANTIES, NOR ASSUMES ANY LIABILITY, FOR ITS USE.

Date of Preparation/ Last Revision: 8/21/2015