

Safety Data Sheet

I. Product and Company Identification

PRODUCT: ISO-FLEX 735 PART A
MANUFACTURER: LymTal International, Inc.
4150 S. Lapeer Rd. Orion, MI 48359
www.lymtal.com
For Non-Emergency Questions,
Hours 8AM To 4PM Eastern Standard Time
(248) 373-8100

EMERGENCY CONTACT: 24-Hour Chemtrec (800)424-9300
Chemtrec, D.C. Area (800)483-7616

II. Hazards Identification

Classification of the Substance or Mixture:



Resp Sensitizer, CAT 1A; Germ Cell Mutagenicity, CAT 1B; Carcinogenicity, CAT 2; STOT Repeated Exposure, CAT 2 Liver, Kidney, CNS; Aspiration Hazard, CAT 2

Signal Word: **DANGER**

Hazard Statements:

H303	May Be Harmful If Swallowed	Acute Toxicity, Cat 5
H305	May Be Harmful If Swallowed and Enters Airways	Aspiration Hazard, Cat 2
H316	Causes Mild Skin Irritation	Skin Corrosion/Irritation Cat 3
H317	May Cause An Allergic Skin Reaction	Skin Sensitizer, Cat 1
H320	Causes Eye Irritation	Eye Damage/Irritation, Cat 2B
H332	Harmful if Inhaled	Acute Toxicity, Cat 4, Inhale
H334	May Cause Allergy Or Asthma Symptoms Or Breathing Difficulties If Inhaled	Resp Sensitizer, Cat 1A
H335	May Cause Respiratory Irritation	Stot Single Exposure, Cat 3A, Respiratory Irritant
H336	May Cause Drowsiness Or Dizziness	Stot Single Exposure, Cat 3B, Narcotic Effects
H340	May Cause Genetic Defects	Germ Cell Mutagenicity , Cat 1B
H351	Suspected Of Causing Cancer	Carcinogenicity, Cat 2
H373	May Cause Damage To Organs Through Prolonged Or repeated Exposure	Stot Repeated Exposure, Cat 2, Liver, Kidney, CNS
H402	Harmful To Aquatic Life	Aquatic Environmental Hazard, Cat 3
H412	Harmful To Aquatic Life With Long Lasting Effects	Long term Aquatic environmental Hazard, Cat 3

Precautionary Statements:

P102	Keep Out Of Reach Of Children
P103	Read Label Before Use
P201	Obtain Special Instructions Before Use

P202	Do Not Handle Until All Safety Precautions Have Been Read And Understood
P260	Do Not Breathe Dust/Fume/Gas/Mist/Vapors/Spray
P264	Wash Thoroughly After Handling
P270	Do Not Eat/Drink/Smoke While Using This Product
P271	Use Only Outdoors Or In A Well Ventilated Area
P272	Contaminated Clothing Should Not Be Allowed Out Of The Workplace
P273	Avoid Release To The Environment
P280	Wear Protective Gloves/Protective Clothing/Eye Protection/Face Protection
P284	Wear Respiratory Protection
P301 +P315	If Swallowed: Get Immediate Medical Advice/Attention
P302 + P362+P353	If On Skin: take Off Contaminated Clothing, Rinse Skin With Water/Shower
P304+P340	If Inhaled: Remove Person To Fresh Air And Keep Comfortable For Breathing
P305+P351+P315	If In Eyes: Rinse Cautiously With Water For Several Minutes, Get Immediate Medical Advice/Attention
P308+P313	If Exposed Or Concerned: Get Medical Advice/Attention
P312	Call A Poison Center/Doctor If You Feel Unwell
P331	Do Not Induce Vomiting
P332+P313	If Skin Irritation Occurs, Get Medical Advice/Attention
P337+P313	If Eye Irritation Persists: Get Medical Advice/Attention
P342+P311	If Experiencing Respiratory Symptoms, Call A Poison Center Or Doctor
P370+P378	In Case Of Fire: Use Carbon Dioxide, Foam, Dry Chemical, Water Fog To Extinguish
P391	Collect Spillage
P403+P235	Store In A Well Ventilated Place. Keep Cool.
P403+P235+P233	Store In A Well Ventilated Place. Keep Cool. Keep Container Tightly Closed
P405	Store Locked Up
P501	Dispose Of Contents/Container In Accordance With Local/Regional/National/International/Regulations

III. Composition/Information on Ingredients

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). Where a proprietary ingredient is shown, the identity may be made available as provided in this standard. All components of this product are included in the EPA Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

<u>Ingredients:</u>	<u>CAS #:</u>	<u>CONTENT</u>
Polyurethane Prepolymer	Proprietary	>97%
Petroleum Hydrocarbons	64742-95-6	1.953%

California Proposition 65 ingredients

None

Section 313 Supplier Notification

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 (40CFR372)

1,2,4-Trimethylbenzene	95-63-6	0.992%
Xylene	1330-20-7	0.093%
Cumene	98-82-8	0.0465%
Ethylbenzene	100-41-4	0.0155%
Isophorone Diisocyanate	4098-71-9	<1%

IV. First Aid Measures

<u>Inhalation</u>	Remove victim from exposure. If difficulty with breathing, administer oxygen and seek medical assistance
<u>Eyes</u>	Flush eyes with cold water for a minimum of 15 minutes, lifting lower and upper eye lids throughout. Seek immediate medical attention.
<u>Skin</u>	Immediately remove contaminated clothing. Wash thoroughly with soap and water. If irritation persists seek medical attention. Wash contaminated clothing before reuse.
<u>Ingestion</u>	Do not induce vomiting; get immediate medical attention, if vomiting occurs spontaneously keep head below hips to prevent aspiration of liquids into lungs. Do not give anything by mouth to an unconscious person

V. Fire Fighting Methods

HMIS Hazard Rating No. 1

Flash Point: > 93 °C (200 °F)

Method: Pensky Martin C.C.

General Hazard: Decomposition and combustion products may be toxic.

Auto-Ignition Temp.: Not Available

Limits of Flammability

LEL: Not Available

UEL: Not Available

Extinguishing Media

Use foam, carbon dioxide, or dry chemical.

Special Fire & Unusual Hazards

Move containers from area if it can be done without risk. Cool fire-exposed containers with water from the side. As in any fire, wear NIOSH/MSHA approved, pressure demand self contained breathing apparatus and full protective gear.

VI. Accidental Release Measures

Action To Take For Spills/ Leaks: Avoid contact with skin or eyes. Ventilate area, and eliminate all sources of ignition. Wear appropriate protective gear, contain leak or spill, salvage, clean up residue with absorbent material.

Waste Disposal Method: Handle disposal of waste material in manner that complies with local, state, province and federal regulation. Landfill if solidified, or incineration at agency approved waste-disposal facilities.

VII. Handling And Storage

Store at ambient room temperature

VIII. Exposure Controls / Personal Protection

Ventilation: Ventilation is recommended. Air movement must be designed to insure turnover at all locations in work area to avoid build up of heavy vapors.

Personal Protection Equipment: Do NOT wear contact lenses when working with this material. Use chemical goggles/safety glasses with side shields and impervious gloves. Wear clothing with long sleeves and pants. In operations where mists can be generated or the exposure limits for crystalline silica exceeded, wear a NIOSH/MSHA approved dust/fume respirator selected by a technically qualified person for the specific work conditions. Wear respirator protection whenever airborne concentrations exceed TLV ceilings or TWA, use NIOSH approved respirators for listed hazard.

Confined spaces, room, or tanks are areas where concern for TLV's is especially important. Reference OSHA regulation CFR 29 1910.134 for recommended respiratory protection.

IX. Physical And Chemical Properties

Boiling Point (°C):	N/D	Water/Oil Distribution Coefficient:	N/A
Volatile Organic Content	40 g / l	Solubility in Water:	Reacts in v
Freezing Point (°C):	N/A	Specific Gravity @20° C	1.02
Vapor Pressure @ 20° C	N/A	pH:	N/A
Vapor Density	>1	Evaporation Rate:	N/A
Odor Threshold:	N/A	Odor:	Aromatic
Appearance:	Amber liquid		
N/A = Not Available	N/D=NOT Determined	Ca. = Approximate	

X. Stability And Reactivity

HMIS Hazard Rating No. 1

Stability

Stable

Incompatibility:

Water, alcohol, amines, bases and acids

Hazardous Decomposition Products

Oxides of Carbon; nitrogen and HCN. Decomposition and Combustion products may be toxic.

Conditions To Avoid

Strong acids in bulk.

XI. Toxicity Information

HMIS Hazard Rating No. 2

PRIMARY ROUTE OF ENTRY: Inhalation, dermal, skin and eye contact.

Effects Of Overexposure

Inhalation:

Vapors may be irritating to the upper respiratory tract.

Eyes:

Contact can cause severe irritation.

Skin Contact:

Irritating to the skin. In some individuals it may cause sensitization.

Ingestion:

May cause permanent damage to the mouth throat and stomach.

Chronic:

This product does not contain chemicals considered to be carcinogenic by NTP, IRAC, ACGIH, OSHA.

XII. Ecological Information

Marine Pollutant: NL

(NL = Not Listed; P = Moderate; PP = Severe; ND = Not Determined)

XIII. Disposal Considerations

Handle disposal of waste material in a manner that complies with all applicable local, state, provincial and federal regulations.

XIV. Transport Information

DOT SHIPPING INFORMATION

DOT Proper Shipping Name NOT REGULATED

DOT Hazard Class

DOT I.D Number

Label(s)

XV. Regulatory Information

OSHA Hazard Communication Standard (29 CFR 1910.1200)	Hazardous
CERCLA/ Super fund (40 CFR 117,302)	N/A
SARA Extremely Hazardous Substances (40 CFR 355)	N/A
SARA Hazard Categories (40 CFR 370)	Health : Immediate Physical: Fire
SARA Toxic Chemicals (40 CFR 372) Inventory Status	See section 313 supplier notification The chemicals in this product are listed on the US TSCA Chemical Substance Inventory and the Canadian Domestic Substances List.

XVI. Other Information

THE INFORMATION HEREIN HAS BEEN COMPLIED FROM SOURCES BELIEVED TO BE RELIABLE AND IS ACCURATE TO THE BEST OF OUR KNOWLEDGE. HOWEVER, LymTal INTERNATIONAL INC. CANNOT GIVE ANY GUARANTEES REGARDING INFORMATION FROM OTHER SOURCES, AND EXPRESSLY DOES NOT MAKE ANY WARRANTIES, NOR ASSUMES ANY LIABILITY, FOR ITS USE.

Date of Preparation/ Last Revision: 7/11/2015

Safety Data Sheet

I. Product and Company Identification

PRODUCT: ISO-FLEX 735 PART B
MANUFACTURER: LymTal International, Inc.
4150 S. Lapeer Rd. Orion, MI 48359
www.lymtal.com
For Non-Emergency Questions,
Hours 8AM To 4PM Eastern Standard Time
(248) 373-8100

EMERGENCY CONTACT: 24-Hour Chemtrec (800)424-9300
Chemtrec, D.C. Area (800)483-7616

II. Hazards Identification

Classification of the Substance or Mixture:



STOT Single Exposure, CAT 3A, Respiratory Irritant; Eye Damage/Irritation, CAT 2A



Resp Sensitizer, CAT 1B; Germ Cell Mutagenicity, CAT 1B; Carcinogenicity, CAT 2; STOT Repeated Exposure, CAT 2, Liver Kidney, CNS, Pancreas; Aspiration Hazard, CAT 2

Signal Word:

DANGER

Hazard Statements:

H227	Combustible Liquid	Flammable Liquid, Cat 4
H303	May Be Harmful If Swallowed	Acute Toxicity, Cat 5, Oral
H304	May Be Fatal If Swallowed and Enters Airways	Aspiration Hazard, Cat 1
H316	Causes Mild Skin Irritation	Skin Corrosion/Irritation Cat 3
H319	Causes Serious Eye Irritation	Eye Damage/Irritation, Cat 2A
H334	May Cause Allergy Or Asthma Symptoms Or Breathing Difficulties If Inhaled	Resp Sensitizer, Cat 1B
H335	May Cause Respiratory Irritation	Stot Single Exposure, Cat 3A, Liver, Kidney, CNS, Pancreas
H340	May Cause Genetic Defects	Germ Cell Mutagenicity, Cat 1B
H351	Suspected Of Causing Cancer	Carcinogenicity, Cat 2
H373	May Cause Damage To Organs Through Prolonged Or repeated Exposure	Stot Repeated Exposure, Cat 2, Sore Throat
H401	Toxic To Aquatic Life	Aquatic Environmental Hazard, Cat 2
H412	Harmful To Aquatic Life With Long Lasting Effects	Long term Aquatic environmental Hazard, Cat 3

Precautionary Statements:

P102 Keep Out Of Reach Of Children
P103 Read Label Before Use

P201	Obtain Special Instructions Before Use
P202	Do Not Handle Until All Safety Precautions Have Been Read And Understood
P210	Keep Away From Heat, Hot Surfaces, Sparks, Open Flames And Other Ignition Sources No Smoking
P233	Keep Container Tightly Closed
P260	Do Not Breathe Dust/Fume/Gas/Mist/Vapors/Spray
P264	Wash Thoroughly After Handling
P270	Do Not Eat/Drink/Smoke While Using This Product
P271	Use Only Outdoors Or In A Well Ventilated Area
P272	Contaminated Clothing Should Not Be Allowed Out Of The Workplace
P273	Avoid Release To The Environment
P280	Wear Protective Gloves/Protective Clothing/Eye Protection/Face Protection
P285	In Case Of Inadequate Ventilation Wear Respiratory Protection
P301 +P315	If Swallowed: Get Immediate Medical Advice/Attention
P302 + P362+P353	If On Skin: take Off Contaminated Clothing, Rinse Skin With Water/Shower
P304+P340	If Inhaled: Remove Person To Fresh Air And Keep Comfortable For Breathing
P305+P351+P315	If In Eyes: Rinse Cautiously With Water For Several Minutes, Remove Contact Lenses If Present And Easy To Do. Continue Rinsing.
P308+P313	If Exposed Or Concerned: Get Medical Advice/Attention
P312	Call A Poison Center/Doctor If You Feel Unwell
P331	Do Not Induce Vomiting
P332+P313	If Skin Irritation Occurs, Get Medical Advice/Attention
P342+P311	If Experiencing Respiratory Symptoms, Call A Poison Center Or Doctor
P337+P313	If Eye Irritation Persists: Get Medical Advice/Attention
P370+P378	In Case Of Fire: Use Carbon Dioxide, Foam, Dry Chemical, Water Fog To Extinguish
P391	Collect Spillage
P403+P235	Store In A Well Ventilated Place. Keep Cool.
P405	Store Locked Up
P501	Dispose Of Contents/Container In Accordance With Local/Regional/National/International/ Regulations

III. Composition/Information on Ingredients

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). Where a proprietary ingredient is shown, the identity may be made available as provided in this standard. All components of this product are included in the EPA Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

<u>Ingredients:</u>	<u>CAS #:</u>	<u>CONTENT</u>
Diethyltoluenediamine	68479-98-1	<10%
Petroleum Hydrocarbons	64742-95-6	3.276%
Proprietary Ingredients		Balance

California Proposition 65 ingredients

None

Section 313 Supplier Notification

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 (40CFR372)

1,2,4 Trimethylbenzene	95-63-6	1.664%
Xylene	1330-20-7	0.156%
Cumene	98-82-8	0.078%
Ethyl Benzene	100-41-4	0.026%

IV. First Aid Measures

<u>Inhalation</u>	Remove victim from exposure. If difficulty with breathing, administer oxygen and seek medical assistance
<u>Eyes</u>	Flush eyes with cold water for a minimum of 15 minutes, lifting lower and upper eye lids throughout. Seek immediate medical attention.
<u>Skin</u>	Immediately remove contaminated clothing. Wash thoroughly with soap and water. If irritation persists seek medical attention. Wash contaminated clothing before reuse.
<u>Ingestion</u>	Do not induce vomiting; get immediate medical attention, if vomiting occurs spontaneously keep head below hips to prevent aspiration of liquids into lungs. Do not give anything by mouth to an unconscious person

V. Fire Fighting Methods

HMIS Hazard Rating No. 1

Flash Point: 93 °C (200 °F)

Method: Cleveland O.C.

General Hazard: Decomposition and combustion products may be toxic.

Auto-Ignition Temp.: Not Available

Limits of Flammability

LEL: Not Available

UEL: Not Available

Extinguishing Media

Use water spray, foam, CO₂, or dry chemical.

Special Fire & Unusual Hazards

Move containers from area if it can be done without risk. Cool fire-exposed containers with water from the side. As in any fire, wear NIOSH/MSHA approved, pressure demand self contained breathing apparatus and full protective gear.

VI. Accidental Release Measures

Action To Take For Spills/ Leaks: Avoid contact with skin or eyes. Ventilate area, and eliminate all sources of ignition. Wear appropriate protective gear, contain leak or spill, salvage, clean up residue with absorbent material.

Waste Disposal Method: Handle disposal of waste material in manner that complies with local, state, province and federal regulation. Landfill if solidified or incineration at agency approved waste-disposal facilities.

VII. Handling And Storage

Store In A Cool, Dry Place At 50-95°F. Condition Material To 65-85°F Before Using

VIII. Exposure Controls / Personal Protection

Ventilation: Ventilation is recommended. Air movement must be designed to insure turnover at all locations in work area to avoid build up of heavy vapors.

Personal Protection Equipment: Do NOT wear contact lenses when working with this material. Use chemical goggles/safety glasses with side shields and impervious gloves. Wear clothing with long sleeves and pants. In operations where mists can be generated or the exposure limits for crystalline silica exceeded, wear a NIOSH/MSHA approved dust/fume respirator selected by a technically qualified person for the specific work conditions. Wear respirator protection whenever airborne concentrations exceed TLV ceilings or TWA, use NIOSH approved respirators for listed hazard.

Confined spaces, room, or tanks are areas where concern for TLV's is especially important. Reference OSHA regulation CFR 29 1910.134 for recommended respiratory protection.

IX. Physical And Chemical Properties

Boiling Point (°C):	232	Water/Oil Distribution Coefficient:	N/A
Percent Volatile:	5.2% (40 g / l, a + b)	Solubility in Water:	Negligible
Freezing Point (°C):	N/A	Specific Gravity @20° C	0.98
Vapor Pressure @ 20° C	N/A	pH:	N/A
Vapor Density	> air	Evaporation Rate:	N/A
Odor Threshold:	N/A	Odor:	Ammonical
Appearance:	Pigmented paste		
N/A = Not Available	N/D=NOT Determined	Ca. = Approximate	

X. Stability And Reactivity

HMIS Hazard Rating No. 0

Stability

Stable

Incompatibility:

Peroxide, oxidizing and reducing agents and flames.

Hazardous Decomposition Products

Oxides of Carbon; and nitrogen. Decomposition and Combustion products may be toxic.

Conditions To Avoid

See incompatibility section.

XI. Toxicity Information

HMIS Hazard Rating No. 1

PRIMARY ROUTE OF ENTRY: Inhalation, dermal, eyes

Effects Of Overexposure

Inhalation:

Vapor inhalation may cause irritation to the respiratory tract.

Eyes:

Contact can cause mild irritation.

Skin Contact:

Contact can cause mild irritation.

Ingestion:

Not expected to be a relevant route of exposure although it may cause gastrointestinal irritation, nausea, vomiting, diarrhea, headache, and drowsiness.

Chronic:

This product does not contain chemicals considered to be carcinogenic by NTP, IRAC, ACGIH, OSHA.

XII. Ecological Information

Marine Pollutant: NL

(NL = Not Listed; P = Moderate; PP = Severe; ND = Not Determined)

XIII. Disposal Considerations

Handle disposal of waste material in a manner that complies with all applicable local, state, provincial and federal regulations.

XIV. Transport Information

DOT SHIPPING INFORMATION

DOT Proper Shipping Name NOT REGULATED

XV. Regulatory Information

OSHA Hazard Communication Standard (29 CFR 1910.1200)	Hazardous
CERCLA/ Super fund (40 CFR 117,302)	N/A
SARA Extremely Hazardous Substances (40 CFR 355)	N/A
SARA Hazard Categories (40 CFR 370)	Health : Immediate Physical: Delayed
SARA Toxic Chemicals (40 CFR 372) Inventory Status	See section 313 advisory in section II The chemicals in this product are listed on the US TSCA Chemical Substance Inventory and the Canadian Domestic Substances List.

XVI. Other Information

THE INFORMATION HEREIN HAS BEEN COMPLIED FROM SOURCES BELIEVED TO BE RELIABLE AND IS ACCURATE TO THE BEST OF OUR KNOWLEDGE. HOWEVER, LymTal INTERNATIONAL INC. CANNOT GIVE ANY GUARANTEES REGARDING INFORMATION FROM OTHER SOURCES, AND EXPRESSLY DOES NOT MAKE ANY WARRANTIES, NOR ASSUMES ANY LIABILITY, FOR ITS USE.

Date of Preparation/ Last Revision: 7/11/2015