

Safety Data Sheet

I. Product and Company Identification

PRODUCT: ISOFLEX 760 INTERMEDIATE COAT PART A

MANUFACTURER: LymTal International, Inc.
4150 S. Lapeer Rd. Orion, MI 48359
www.lymtal.com
For Non-Emergency Questions,
Hours 8AM To 4PM Eastern Standard Time
(248) 373-8100

EMERGENCY CONTACT: 24-Hour Chemtrec (800)424-9300
Chemtrec, D.C. Area (800)483-7616

II. Hazards Identification

Classification of the Substance or Mixture:



Resp Sensitizer, CAT 1

Signal Word:

DANGER

Hazard Statements:

H332	Harmful If Inhaled	Acute Toxicity, Cat 4, Inhale
H315	Causes Skin Irritation	Skin Corrosion/Irritation Cat 2
H320	Causes Eye Irritation	Eye Damage/Irritation, Cat 2B
H334	May Cause Allergy Or Asthma Symptoms Or Breathing Difficulties If Inhaled	Resp Sensitizer, Cat 1
H317	May Cause An Allergic Skin Reaction	Skin Sensitizer, Cat 1
H335	May Cause Respiratory Irritation	STOT Single Exposure, CAT 3, RTI

Precautionary Statements:

P102	Keep Out Of Reach Of Children
P103	Read Label Before Use
P202	Do Not Handle Until All Safety Precautions Have Been Read And Understood
P260	Do Not Breathe Dust/Fume/Gas/Mist/Vapors/Spray
P264	Wash Thoroughly After Handling
P270	Do Not Eat/Drink/Smoke While Using This Product
P271	Use Only Outdoors Or In A Well Ventilated Area
P272	Contaminated Work Clothing Should Not Be Allowed Out Of The Workplace
P280	Wear Protective Gloves/Protective Clothing/Eye Protection/Face Protection
P285	In Case Of Inadequate Ventilation Wear Respiratory Protection
P302 + P362+P353	If On Skin: take Off Contaminated Clothing, Rinse Skin With Water/Shower
P309+P311	If Exposed Or If You Feel Unwell: Call A Poison Center Or Doctor
P333+P313	If Skin Irritation Or Rash Occurs, Get Medical Advice/Attention
P342+P311	If Experiencing Respiratory Symptoms: Call A Poison Center Or Doctor
P373+P313	If Eye Irritation Persists: Get Medical Advice/Attention
P363	Wash Contaminated Clothing Before Reuse
P305+P351+P338	If In Eyes: Rinse Cautiously With Water For Several Minutes, Remove Contact Lenses

P304+P340	If Present And Easy To Do. Continue Rinsing. If Inhaled: Remove Person To Fresh Air And Keep Comfortable For Breathing
P403+P233	Store In A Well Ventilated Place. Keep Container Tightly Closed
P405	Store Locked Up
P501	Dispose Of Contents/Container In Accordance With Local//Regional//National//International/ Regulations

III. Composition/Information on Ingredients

<u>Ingredients:</u>	<u>CAS #:</u>	<u>CONTENT</u>
Modified MDI	Not Disclosed	<15.0%
4,4' Diphenylmethane Diisocyanate	101-68-8	60.0-100.0%

California Proposition 65 ingredients

None

Section 313 Supplier Notification

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 (40CFR372)

4,4' Diphenylmethane diisocyanate	101-68-8
-----------------------------------	----------

Modified MDI	Not Disclosed
--------------	---------------

IV. First Aid Measures

<u>Inhalation</u>	Remove victim from exposure. If difficulty with breathing, administer oxygen and seek medical assistance
<u>Eyes</u>	Flush eyes with cold water for a minimum of 15 minutes, lifting lower and upper eye lids throughout. Seek immediate medical attention.
<u>Skin</u>	Immediately remove contaminated clothing. Wash thoroughly with soap and water. If irritation persists seek medical attention. Wash contaminated clothing before reuse.
<u>Ingestion</u>	Do not induce vomiting; get immediate medical attention, if vomiting occurs spontaneously keep head below hips to prevent aspiration of liquids into lungs. Do not give anything by mouth to an unconscious person

V. Fire Fighting Methods

HMIS Hazard Rating No. 1

Flash Point: >200.0 °F

General Hazard: Decomposition and combustion products may be toxic.

Auto-Ignition Temp.: >600 °C

Limits of Flammability

LEL: Not Available

UEL: Not Available

Extinguishing Media

Carbon dioxide, foam, dry chemical and water fog.

Special Fire & Unusual Hazards

Move containers from area if it can be done without risk. Cool fire-exposed containers with water from the side. As in any fire, wear NIOSH/MSHA approved; pressure demand self-contained breathing apparatus and full protective gear. Avoid water contamination in closed containers or confined areas as carbon dioxide is evolved.

VI. Accidental Release Measures

Action To Take For Spills/ Leaks: Avoid contact with skin or eyes. Ventilate area; eliminate all sources of ignition. Wear appropriate protective gear, contain leak or spill, salvage, and clean up residue with absorbent material. Wash down area with dilute ammonium hydroxide or detergent solution; allow 30 minutes to react. For large spills, dike area and pump into closed containers. Prevent this material from entering waterways.

Waste Disposal Method: Handle disposal of waste material in a manner that complies with local, state, province and federal regulation. Landfill if solidified, or incineration at agency approved waste-disposal facilities.

VII. Handling And Storage

Store Dry At 50-95°F. Condition Material To 65-85°F Before Using

VIII. Exposure Controls / Personal Protection

Ventilation: Ventilation is recommended. Air movement must be designed to insure turnover at all locations in work area to avoid build up of heavy vapors.

Personal Protection Equipment: Do NOT wear contact lenses when working with this material. Use chemical goggles/safety glasses with side shields and impervious gloves. Wear clothing with long sleeves and pants. **In operations where mists can be generated or the exposure limits for crystalline silica exceeded, wear a NIOSH/MSHA approved dust/fume respirator selected by a technically qualified person for the specific work conditions.** Wear respirator protection whenever airborne concentrations exceed TLV ceilings or TWA, use NIOSH approved respirators for listed hazard.

Confined spaces, room, or tanks are areas where concern for TLV's is especially important. Reference OSHA regulation CFR 29 1910.134 for recommended respiratory protection.

IX. Physical And Chemical Properties

Boiling Point (°C):	N/A	Water/Oil Distribution Coefficient:	N/A
VOC Content g/l:	< 13 g / L = Pt.A Pt.A + Pt. B = 11 g / L	Solubility in Water:	Reacts with
Freezing Point (°C):	N/A	Specific Gravity @20° C	1.21
Vapor Pressure @ 20° C	4 x 10 ⁻⁶ mmHg	pH:	N/A
Vapor Density	8.5	Evaporation Rate:	N/A
Odor Threshold:	N/A	Odor:	Musty
Appearance:	Amber liquid		
N/A = Not Available	N/D=NOT Determined	Ca. = Approximate	

X. Stability And Reactivity

HMIS Hazard Rating No. 1

Stability

Stable

Incompatibility:

Strong acids, oxidizing agents reducing agents bases water peroxides and amines.

Hazardous Decomposition Products

At elevated temperatures, isocyanate vapors may be formed. Under severe thermal degradation, carbon monoxide and low molecular weight organic compounds may be formed as well as hydrogen cyanide and MDI vapors.

Conditions To Avoid

See incompatibility.

XI. Toxicity Information

HMIS Hazard Rating No. 3

PRIMARY ROUTE OF ENTRY: Eye and skin contact, breathing and ingestion.

Effects Of Overexposure

Inhalation:

Inhalation of MDI vapors may cause irritation of the mucous membranes of the nose, throat, or trachea, breathlessness, chest discomfort, and difficulty breathing and reduced pulmonary function. Airborne exposure well above the PEL may result additionally in eye irritation, headache, chemical bronchitis, and asthma like findings or pulmonary edema. Isocyanates have also been reported to cause hypersensitivity pneumonitis, which is characterized by flu like symptoms, the onset of which may be delayed.

Eyes:

Contact can cause burning and tearing.

Skin Contact:

Contact may cause moderate skin irritation. In some individuals exposure may result in allergic type symptoms causing rash, itching, and hives.

Ingestion:

Not expected to be a relevant route of exposure although it may cause gastrointestinal irritation, nausea, and vomiting and abdominal pain.

Chronic:

Results from a lifetime study in rats indicate that MDI aerosol was carcinogenic at 6mg/m³, the highest dose tested. This is well above the recommended TLV of 5ppb (0.05mg/m³). Only irritation was noted at the lower concentrations of 0.2 and 1 mg/m³. No birth defects or teratogenic effects were reported in a teratology study with rats exposed to 1, 4, and 12mg/m³ polymeric MDI for 6hr/day on days 6 – 15 of gestation. As a result of repeated overexposure or a single large dose, certain individuals will develop isocyanate sensitization (chemical asthma) which will cause them to react to a later exposure to isocyanate levels at levels well below the PEL / TLV. These symptoms include chest tightness, wheezing, cough, shortness of breath, or asthma attack, which could be immediate or occur several hours after exposure. Chronic overexposure to isocyanates has also been reported to cause lung damage, including a decrease in lung function, which may be permanent.

XII. Ecological Information

Marine Pollutant: NL

(NL = Not Listed; P = Moderate; PP = Severe; ND = Not Determined)

XIII. Disposal Considerations

Handle disposal of waste material in a manner that complies with all applicable local, state, provincial and federal regulations.

XIV. Transport Information

DOT SHIPPING INFORMATION

DOT Proper Shipping Name **NOT REGULATED**

DOT Hazard Class

DOT I.D Number

Label(s)

XV. Regulatory Information

OSHA Hazard Communication Standard
(29 CFR 1910.1200)
CERCLA/ Super fund (40 CFR 117,302)

Hazardous

N/A

SARA Extremely Hazardous Substances
(40 CFR 355)
SARA Hazard Categories (40 CFR 370)
SARA Toxic Chemicals (40 CFR 372)
Inventory Status
4,4' Diphenylmethane diisocyanate
CAS # 101-68-8, RQ is 5000 lbs.

N/A

See section III ~~supplier notification~~

The chemicals in this product are listed on the US TSCA Chemical Substance Inventory and the Canadian Domestic Substances List.

**REPORTABLE QUANTITY = 5000 LBS. (MDI)
SINGLE CONTAINER, IF SINGLE CONTAINER
LESS THAN 5000 LBS. THEN
NOT REGULATED.**

XVI. Other Information

THE INFORMATION HEREIN HAS BEEN COMPLIED FROM SOURCES BELIEVED TO BE RELIABLE AND IS ACCURATE TO THE BEST OF OUR KNOWLEDGE. HOWEVER, LymTal INTERNATIONAL INC. CANNOT GIVE ANY GUARANTEES REGARDING INFORMATION FROM OTHER SOURCES, AND EXPRESSLY DOES NOT MAKE ANY WARRANTIES, NOR ASSUMES ANY LIABILITY, FOR ITS USE.

Date of Preparation/ Last Revision: 11/20/2018

Safety Data Sheet

I. Product and Company Identification

PRODUCT: ISO FLEX 760 INTERMEDIATE PART B

MANUFACTURER: LymTal International, Inc.
4150 S. Lapeer Rd. Orion, MI 48359
www.lymtal.com
For Non-Emergency Questions,
Hours 8AM To 4PM Eastern Standard Time
(248) 373-8100

EMERGENCY CONTACT: 24-Hour Chemtrec (800)424-9300
Chemtrec, D.C. Area (800)483-7616

II. Hazards Identification

Classification of the Substance or Mixture:



Skin Corrosion/Irritation, CAT 2; Skin Sensitizer, CAT 1; STOT Single Exposure, CAT 3, RTI;
STOT Single Exposure, CAT 3, NE/CNS



Reproduction Toxicity, CAT 1

Signal Word:

DANGER

Hazard Statements:

H315	Causes Skin Irritation	Skin Corrosion/Irritation Cat 2
H317	May Cause An Allergic Skin Reaction	Skin Sensitizer, Cat 1
H320	Causes Eye Irritation	Eye Damage/Irritation, Cat 2B
H335	May Cause Respiratory Irritation	STOT Single Exposure, Cat 3, NE/CNS
H336	May Cause Drowsiness Or Dizziness	STOT Single Exposure, Cat 3, RTI
H360	May Damage Fertility Or The Unborn Baby	Reproduction Toxicity, Cat 1

Precautionary Statements:

P101	If Medical Advice Is Needed, Have Product Container Or Label At Hand
P102	Keep Out Of Reach Of Children
P103	Read Label Before Use
P201	Obtain Special Instructions Before Use
P202	Do Not Handle Until All Safety Precautions Have Been Read And Understood
P261	Avoid Breathing Vapors
P264	Wash Thoroughly After Handling
P270	Do Not Eat/Drink/Smoke While Using This Product
P271	Use Only Outdoors Or In A Well Ventilated Area
P272	Contaminated Clothing Should Not Be Allowed Out Of The Workplace
P273	Avoid Release To The Environment
P280	Wear Protective Gloves/Protective Clothing/Eye Protection/Face Protection
P301+P310	If Swallowed: Immediately Call A Poison Center Or Doctor/Physician
P303+P313	If Exposed Or Concerned: Get Medical Advice/Attention

P337+P313 If Eye Irritation Persists: Get Medical Advice/Attention
P331 Do Not Induce Vomiting
P302 + P362+P353 If On Skin: take Off Contaminated Clothing, Rinse Skin With Water/Shower
P332+P313 If Skin Irritation Occurs, Get Medical Advice/Attention
P305+P351+P315 If In Eyes: Rinse Cautiously With Water For Several Minutes, Get Immediate Medical Advice/Attention
P304+P340+P314 If Inhaled: Remove Person To Fresh Air And Keep Comfortable For Breathing, Get Medical Advice/Attention If You Feel Unwell.
P362+P364 Take Off: Contaminated Clothing And Wash It Before Reuse
P403+P233 Store In A Well Ventilated Place And Keep Container Tightly Closed
P405 Store Locked Up
P501 Dispose Of Contents/Container In Accordance With Local/Regional/National/International/Regulations

III. Composition/Information on Ingredients

Ingredients:	CAS #:	CONTENT
N-Methylpyrrolidone	872-50-4	<3.0%
Magnesium Silicate	14807-96-6	<10.0%
Proprietary Ingredients		Balance

California Proposition 65 ingredients

N-methyl pyrrolidone	872-50-4
Ethyl acrylate	140-88-5
1,4-dioxane	123-91-1
Ethyl benzene	100-41-4

Section 313 Supplier Notification

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 (40CFR372)

N-methyl pyrrolidone	872-50-4
Ethyl acrylate	140-88-5
1,4-dioxane	123-91-1
Ethyl benzene	100-41-4

IV. First Aid Measures

Inhalation Remove victim from exposure. If difficulty with breathing, administer oxygen and seek medical assistance

Eyes Flush eyes with cold water for a minimum of 15 minutes, lifting lower and upper eye lids throughout. Seek immediate medical attention.

Skin Immediately remove contaminated clothing. Wash thoroughly with soap and water. If irritation persists seek medical attention. Wash contaminated clothing before reuse.

Ingestion Do not induce vomiting; get immediate medical attention, if vomiting occurs spontaneously keep head below hips to prevent aspiration of liquids into lungs. Do not give anything by mouth to an unconscious person

V. Fire Fighting Methods

HMIS Hazard Rating No. 2

Flash Point: >500.0 °F

General Hazard: Decomposition and combustion products may be toxic.

Auto-Ignition Temp.: 800 °F

Limits of Flammability

LEL: Not Available

UEL: Not Available

Extinguishing Media

Carbon dioxide, foam, dry chemical and water fog.

Special Fire & Unusual Hazards

Move containers from area if it can be done without risk. Cool fire-exposed containers with water from the side. As in any fire, wear NIOSH/MSHA approved, pressure demand self contained breathing apparatus and full protective gear.

VI. Accidental Release Measures

Action To Take For Spills/ Leaks: Avoid contact with skin or eyes. ventilate area, and eliminate all sources of ignition. Wear appropriate protective gear, contain leak or spill, salvage, clean up residue with absorbent material. Wash down the area with dilute ammonium hydroxide, or detergent solution, allow 30 minutes to react. For large spills, dike area and pump into closed containers. Prevent this material from entering waterways.

Waste Disposal Method: Handle disposal of waste material in manner which complies with local, state, province and federal regulation. Landfill if solidified, or incineration at agency approved waste-disposal facilities.

VII. Handling And Storage

Store In A Cool, Dry, Well Ventilated Area Away From Strong Oxidizers and Acids

VIII. Exposure Controls / Personal Protection

Ventilation: Ventilation is recommended. Air movement must be designed to insure turnover at all locations in work area to avoid build up of heavy vapors.

Personal Protection Equipment: Do NOT wear contact lenses when working with this material. Use chemical goggles/safety glasses with side shields and impervious gloves. Wear clothing with long sleeves and pants. In operations where mists can be generated or the exposure limits can be exceeded, wear a NIOSH/MSHA approved dust/fume respirator selected by a technically qualified person for the specific work conditions. Wear respirator protection whenever airborne concentrations exceed TLV ceilings or TWA, use NIOSH approved respirators for listed hazard.

Confined spaces, room, or tanks are areas where concern for TLV's is especially important. Reference OSHA regulation CFR 29 1910.134 for recommended respiratory protection.

IX. Physical And Chemical Properties

Boiling Point (°C):	N/A	Water/Oil Distribution Coefficient:	N/A
VOC Content g/l:	<10 g / L = Pt.B Pt.A + Pt. B = 11 g / L	Solubility in Water:	slight
Freezing Point (°C):	N/A	Specific Gravity @20° C	1.04
Vapor Pressure @ 20° C	N/A	pH:	N/A
Vapor Density	N/A	Evaporation Rate:	N/A
Odor Threshold:	N/A	Odor:	Aromatic
Appearance:	Gray liquid		
N/A = Not Available	N/D=NOT Determined	Ca. = Approximate	

X. Stability And Reactivity

HMIS Hazard Rating No. 1

Stability

Stable

Incompatibility:

Oxidizing agents, and strong acids (nitric, sulfuric)

Hazardous Decomposition Products

Under severe thermal degradation, carbon monoxide and low molecular weight organic compounds may be formed as well as dense smoke.

Conditions To Avoid

See incompatibility.

XI. Toxicity Information

HMIS Hazard Rating No. 1

PRIMARY ROUTE OF ENTRY: Inhalation, dermal

Effects Of Overexposure

Inhalation:

Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly leading to death. Vapors can be irritating to the nose and mucous membranes. High exposures may result in a narcotic effect and headaches.

Eyes:

Contact can cause severe irritation redness, blurred vision, burning and tearing.

Skin Contact:

Contact may cause moderate skin irritation. In some individuals exposure may result in allergic type symptoms causing rash, itching, and hives.

Ingestion:

Not expected to be a relevant route of exposure. Long term effects are not known.

Chronic:

Not Known.

XII. Ecological Information

Marine Pollutant: NL

(NL = Not Listed; P = Moderate; PP = Severe; ND = Not Determined)

XIII. Disposal Considerations

Handle disposal of waste material in a manner that complies with all applicable local, state, provincial and

federal regulations.

XIV. Transport Information

DOT SHIPPING INFORMATION

DOT Proper Shipping Name **NOT REGULATED**

DOT Hazard Class

DOT I.D Number

Label(s)

XV. Regulatory Information

OSHA Hazard Communication Standard
(29 CFR 1910.1200)

Hazardous

CERCLA/ Super fund (40 CFR 117,302)

N/A

SARA Extremely Hazardous Substances
(40 CFR 355)

N/A

SARA Hazard Categories (40 CFR 370)

See section III supplier notification

SARA Toxic Chemicals (40 CFR 372)

The chemicals in this product are listed on the US
TSCA Chemical Substance Inventory and the
Canadian Domestic Substances List.

Inventory Status

California Proposition 65:

See section III for list of chemicals

XVI. Other Information

THE INFORMATION HEREIN HAS BEEN COMPILED FROM SOURCES BELIEVED TO BE RELIABLE AND IS ACCURATE TO THE BEST OF OUR KNOWLEDGE. HOWEVER, LymTal INTERNATIONAL INC. CANNOT GIVE ANY GUARANTEES REGARDING INFORMATION FROM OTHER SOURCES, AND EXPRESSLY DOES NOT MAKE ANY WARRANTIES, NOR ASSUMES ANY LIABILITY, FOR ITS USE.

Date of Preparation/ Last Revision: 11/20/2018