

# Safety Data Sheet

## I. Product and Company Identification

**PRODUCT:** ISO-FLEX PRIMER 750, PART A  
**MANUFACTURER:** LymTal International, Inc.  
4150 S. Lapeer Rd. Orion, MI 48359  
www.lymtal.com  
For Non-Emergency Questions,  
Hours 8AM To 4PM Eastern Standard Time  
(248) 373-8100

**EMERGENCY CONTACT:** 24-Hour Chemtrec (800)424-9300  
Chemtrec, D.C. Area (800)483-7616

## II. Hazards Identification

Classification of the Substance or Mixture:



Flammable Liquid, CAT 3



Resp Sensitizer, CAT 1; Carcinogenicity, CAT 2

Signal Word: **DANGER**

Hazard Statements:

|      |                                                                           |                                 |
|------|---------------------------------------------------------------------------|---------------------------------|
| H226 | Flammable Liquid And Vapor                                                | Flammable Liquid, Cat 3         |
| H315 | Causes Skin Irritation                                                    | Skin Corrosion/Irritation Cat 2 |
| H317 | May Cause An Allergic Skin Reaction                                       | Skin Sensitizer, Cat 1          |
| H319 | Causes Serious Eye Irritation                                             | Eye Damage/Irritation, Cat 2A   |
| H332 | Harmful If Inhaled                                                        | Acute Toxicity, Cat 4           |
| H334 | May Cause Allergy Or Asthma Symptoms Or Breathing Difficulties If Inhaled | Resp Sensitizer, Cat 1          |
| H351 | Suspected Of Causing Cancer                                               | Carcinogenicity, Cat 2          |

Precautionary Statements:

|      |                                                                                                 |
|------|-------------------------------------------------------------------------------------------------|
| P102 | Keep Out Of Reach Of Children                                                                   |
| P103 | Read Label Before Use                                                                           |
| P202 | Do Not Handle Until All Safety Precautions Have Been Read And Understood                        |
| P210 | Keep Away From Heat, Hot Surfaces, Sparks, Open Flames And Other Ignition Sources<br>No Smoking |
| P240 | Ground/Bond Container And Receiving Equipment                                                   |
| P241 | Use Explosion Proof Electrical/Ventilation/Lighting/Equipment                                   |

|                  |                                                                                                                             |
|------------------|-----------------------------------------------------------------------------------------------------------------------------|
| P242             | Use Only Non Sparking Tools                                                                                                 |
| P243             | Take Precautionary Measures Against Static Discharge                                                                        |
| P260             | Do Not Breathe Dust/Fume/Gas/Mist/Vapors/Spray                                                                              |
| P264             | Wash Thoroughly After Handling                                                                                              |
| P270             | Do Not Eat/Drink/Smoke While Using This Product                                                                             |
| P271             | Use Only Outdoors Or In A Well Ventilated Area                                                                              |
| P272             | Contaminated Work Clothing Should Not Be Allowed Out Of The Workplace                                                       |
| P280             | Wear Protective Gloves/Protective Clothing/Eye Protection/Face Protection                                                   |
| P284             | Wear Respiratory Protection                                                                                                 |
| P301 +P315       | If Swallowed: Get Immediate Medical Advice/Attention                                                                        |
| P302 + P362+P353 | If On Skin: take Off Contaminated Clothing, Rinse Skin With Water/Shower                                                    |
| P304+P340+P314   | If Inhaled: Remove Person To Fresh Air And Keep Comfortable For Breathing, Get Medical Advice/Attention If You Feel Unwell. |
| P305+P351+P315   | If In Eyes: Rinse Cautiously With Water For Several Minutes, Get Immediate Medical Advice                                   |
| P309+P311        | If Exposed Or If You Feel Unwell: Call A Poison Center Or Doctor                                                            |
| P330             | Rinse Mouth                                                                                                                 |
| P331             | Do Not Induce Vomiting                                                                                                      |
| P332+P313        | If Skin Irritation Occurs, Get Medical Advice/Attention                                                                     |
| P337+P313        | If Eye Irritation Persists: Get Medical Attention                                                                           |
| P363             | Wash Contaminated Clothing Before Reuse                                                                                     |
| P370+P378        | In Case Of Fire: Use Carbon Dioxide, Foam, Dry Chemical, Water Fog To Extinguish                                            |
| P403+P233        | Store In A Well Ventilated Place. Keep Container Tightly Closed                                                             |
| P405             | Store Locked Up                                                                                                             |
| P501             | Dispose Of Contents/Container In Accordance With Local/Regional/National/International/Regulations                          |

### III. Composition/Information on Ingredients

| <u>Ingredients:</u>                       | <u>CAS #:</u> | <u>CONTENT</u> |
|-------------------------------------------|---------------|----------------|
| Propylene Glycol Monomethyl Ether Acetate | 108-65-6      | 10-20%         |
| Xylene                                    | 1330-20-7     | 10-20%         |
| Ethyl Benzene                             | 100-41-4      | <=3.3%         |
| Urethane Prepolymer                       | Proprietary   | 60-100%        |
| 2,4-Toluene Diisocyanate                  | 584-84-9      | <=0.4%         |
| 2,6-Toluene Diisocyanate                  | 91-08-7       | <=0.1%         |

#### California Proposition 65 ingredients

|                          |          |        |
|--------------------------|----------|--------|
| Ethyl Benzene            | 100-41-4 | <=3.3% |
| 2,4-Toluene Diisocyanate | 584-84-9 | <=0.4% |
| 2,6-Toluene Diisocyanate | 91-08-7  | <=0.1% |

#### Section 313 Supplier Notification

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 (40CFR372)

|                          |           |        |
|--------------------------|-----------|--------|
| Ethyl Benzene            | 100-41-4  | <=3.3% |
| 2,4-Toluene Diisocyanate | 584-84-9  | <=0.4% |
| 2,6-Toluene Diisocyanate | 91-08-7   | <=0.1% |
| Xylene                   | 1330-20-7 | 10-20% |

## IV. First Aid Measures

|                   |                                                                                                                                                                                                                    |
|-------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <u>Inhalation</u> | Remove victim from exposure. If difficulty with breathing, administer oxygen and seek medical assistance                                                                                                           |
| <u>Eyes</u>       | Flush eyes with cold water for a minimum of 15 minutes, lifting lower and upper eye lids throughout. Seek immediate medical attention.                                                                             |
| <u>Skin</u>       | Immediately remove contaminated clothing. Wash thoroughly with soap and water. If irritation persists seek medical attention. Wash contaminated clothing before reuse.                                             |
| <u>Ingestion</u>  | Do not induce vomiting; get immediate medical attention, if vomiting occurs spontaneously keep head below hips to prevent aspiration of liquids into lungs. Do not give anything by mouth to an unconscious person |

## V. Fire Fighting Methods

HMIS Hazard Rating No. 2

**Flash Point:** 40 °C (104 °F)

General Hazard: Decomposition and combustion products may be toxic.

Auto-Ignition Temp.: Not Available

Limits of Flammability

LEL: 1.0% solvent

UEL: 13.10% solvent

Extinguishing Media

Carbon dioxide, foam, dry chemical and water fog.

Special Fire & Unusual Hazards

Move containers from area if it can be done without risk. Cool fire-exposed containers with water from the side. As in any fire, wear NIOSH/MSHA approved, pressure demand self contained breathing apparatus and full protective gear.

## VI. Accidental Release Measures

Action To Take For Spills/ Leaks: Avoid contact with skin or eyes. ventilate area, and eliminate all sources of ignition. Wear appropriate protective gear, contain leak or spill, salvage, clean up residue with absorbent material. Wash down area with dilute ammonium hydroxide or detergent solution, allow 30 minutes to react. For large spills, dike area and pump into closed containers. Prevent this material from entering waterways.

Waste Disposal Method: Handle disposal of waste material in a manner that complies with local, state, province and federal regulation. Landfill if solidified or incineration at agency approved waste-disposal facilities.

## VII. Handling And Storage

Keep containers closed and stored in a well ventilated area at 60 --80 deg F. Outage of container should be filled with nitrogen. Contamination by moisture or basic compounds can cause dangerous pressure build up in closed containers.

## VIII. Exposure Controls / Personal Protection

Ventilation: Ventilation is recommended. Air movement must be designed to insure turnover at all locations in work area to avoid build up of heavy vapors.

Personal Protection Equipment: Do NOT wear contact lenses when working with this material. Use chemical goggles/safety glasses with side shields and impervious gloves. Wear clothing with long sleeves and pants. In operations where mists can be generated or the exposure limits may be exceeded, wear a NIOSH/MSHA approved dust/fume respirator selected by a technically qualified person for the specific work conditions. Wear respirator protection whenever airborne concentrations exceed TLV ceilings or TWA, use NIOSH approved respirators for listed hazard.

Confined spaces, room, or tanks are areas where concern for TLV's is especially important. Reference OSHA regulation CFR 29 1910.134 for recommended respiratory protection.

## IX. Physical And Chemical Properties

|                         |                     |                                     |                   |
|-------------------------|---------------------|-------------------------------------|-------------------|
| Boiling Point (°C):     | 145                 | Water/Oil Distribution Coefficient: | N/A               |
| <b>VOC Content g/l:</b> | <b>403 g/l max</b>  | Solubility in Water:                | Reacts with water |
| Freezing Point (°C):    | -14                 | <b>Specific Gravity @20° C</b>      | <b>1.15</b>       |
| Vapor Pressure @ 20° C  | 11mbar              | pH:                                 | N/A               |
| Vapor Density           | > air               | Evaporation Rate:                   | N/a               |
| Odor Threshold:         | N/A                 | <b>Odor:</b>                        | <b>Aromatic</b>   |
| <b>Appearance:</b>      | <b>Amber liquid</b> |                                     |                   |
| N/A = Not Available     | N/D=NOT Determined  | Ca. = Approximate                   |                   |

## X. Stability And Reactivity

HMIS Hazard Rating No. 1

### Stability

Stable

### Incompatibility:

Strong acids, oxidizing agents reducing agents bases water peroxides and amines.

### Hazardous Decomposition Products

At elevated temperatures, isocyanate vapors may be formed. Under severe thermal degradation, carbon monoxide and low molecular weight organic compounds may be formed as well as hydrogen cyanide and Isocyanic Acid.

### Conditions To Avoid

See incompatibility.

## XI. Toxicity Information

HMIS Hazard Rating No. 2

PRIMARY ROUTE OF ENTRY: Inhalation, dermal

Effects Of Overexposure

Inhalation: Vapors can be irritating to nose and mucous membranes. High exposures may result in narcotic effect, headaches, tightness or burning in chest and coughing. Respiratory sensitivity may result in asthma-like symptoms and on subsequent exposure even below the TLV.

Eyes: Contact can cause burning and tearing.

Skin Contact: Contact may cause moderate skin irritation. In some individuals exposure may result in allergic type symptoms causing rash, itching, and hives.

Ingestion: Not expected to be a relevant route of exposure although it may cause gastrointestinal irritation, nausea, vomiting and abdominal pain.

Chronic: TDI was listed as a potential animal carcinogenic by NTP and IARC. National Toxicology Program study reported increased tumors in rats and mice via TDI exposure through a tube in the stomach (oral gavage technique); lifetime inhalation studies on animals were negative regarding carcinogenicity. Materials are not known mutagenic, teratogenic, or reproductive health hazards.

## XII. Ecological Information

Marine Pollutant: NL (NL = Not Listed; P = Moderate; PP = Severe; ND = Not Determined)

## XIII. Disposal Considerations

Handle disposal of waste material in a manner that complies with all applicable local, state, provincial and federal regulations.

## XIV. Transport Information

### DOT SHIPPING INFORMATION

DOT Proper Shipping Name Resin solution (contains Xylene, 2,4-TDI, 2-Methoxy-1methylethyl Acetate)  
DOT Hazard Class 3 PG III  
DOT I.D Number UN 1866 Label(s) Flammable  
Liquid

## XV. Regulatory Information

|                                                          |                                                       |             |
|----------------------------------------------------------|-------------------------------------------------------|-------------|
| OSHA Hazard Communication Standard<br>(29 CFR 1910.1200) | Hazardous                                             |             |
| CERCLA/ Super fund (40 CFR 117,302)                      | Xylene                                                | RQ: 100lbs  |
|                                                          | Ethyl Benzene                                         | RQ: 1000lbs |
|                                                          | 2,4-toluene diisocyanate                              | RQ: 100lbs  |
|                                                          | 2,6-toluene diisocyanate                              | RQ: 100lbs  |
| SARA Extremely Hazardous Substances<br>(40 CFR 355)      | 2,4 Toluene diisocyanate                              |             |
| SARA Hazard Categories (40 CFR 370)                      | 2,6 Toluene diisocyanate                              |             |
| SARA Toxic Chemicals (40 CFR 372)                        | Acute health hazard, Chronic Health hazard, Fire Ha   |             |
| Inventory Status                                         | See section III supplier notification                 |             |
|                                                          | The chemicals in this product are listed on the US TS |             |
|                                                          | Chemical Substance Inventory and the Canadian Do      |             |
|                                                          | Substances List.                                      |             |
| California Proposition 65:                               | See section III for list of Chemicals                 |             |

## XVI. Other Information

THE INFORMATION HEREIN HAS BEEN COMPLIED FROM SOURCES BELIEVED TO BE RELIABLE AND IS ACCURATE TO THE BEST OF OUR KNOWLEDGE. HOWEVER, LymTal INTERNATIONAL INC. CANNOT GIVE ANY GUARANTEES REGARDING INFORMATION FROM OTHER SOURCES, AND EXPRESSLY DOES NOT MAKE ANY WARRANTIES, NOR ASSUMES ANY LIABILITY, FOR ITS USE.

Date of Preparation/ Last Revision: 12/05/2018

# Safety Data Sheet

## I. Product and Company Identification

**PRODUCT:** ISO-FLEX PRIMER 750, PART B  
**MANUFACTURER:** LymTal International, Inc.  
4150 S. Lapeer Rd. Orion, MI 48359  
www.lymtal.com  
For Non-Emergency Questions,  
Hours 8AM To 4PM Eastern Standard Time  
(248) 373-8100

**EMERGENCY CONTACT:** 24-Hour Chemtrec (800)424-9300  
Chemtrec, D.C. Area (800)483-7616

## II. Hazards Identification

Classification of the Substance or Mixture:



Flammable Liquid, CAT 2



Germ Cell Mutagenicity, CAT 1B; Carcinogenicity, CAT 1B; Aspiration Hazard, CAT 1



Eye Damage/Irritation, CAT 2A; Skin Corrosion/Irritation, CAT 2; STOT Single Exposure, CAT 3, A/B Narcotic Effect/Respiratory Irritant

Signal Word: **DANGER**

### Hazard Statements:

|      |                                              |                                                      |
|------|----------------------------------------------|------------------------------------------------------|
| H225 | Highly Flammable Liquid And Vapor            | Flammable Liquid, Cat 2                              |
| H304 | May Be Fatal If Swallowed And Enters Airways | Aspiration Hazard, Cat 1                             |
| H315 | Causes Skin Irritation                       | Skin Corrosion/Irritation Cat 2                      |
| H319 | Causes Serious Eye Irritation                | Eye Damage/Irritation, Cat 2A                        |
| H335 | May Cause Respiratory Irritation             | STOT Single Exposure, Cat 3A, Respiratory Irritation |
| H336 | May Cause Drowsiness Or Dizziness            | STOT Single Exposure, Cat 3B, Narcotic Effect        |
| H340 | May Cause Genetic Defects                    | Germ Cell Mutagenicity , Cat 1B                      |
| H350 | May Cause Cancer                             | Carcinogenicity, Cat 1B                              |

### Precautionary Statements:

|      |                                                                                   |
|------|-----------------------------------------------------------------------------------|
| P101 | If Medical Advice Is Needed, Have Product Container Or Label At Hand              |
| P102 | Keep Out Of Reach Of Children                                                     |
| P103 | Read Label Before Use                                                             |
| P202 | Do Not Handle Until All Safety Precautions Have Been Read And Understood          |
| P210 | Keep Away From Heat, Hot Surfaces, Sparks, Open Flames And Other Ignition Sources |

|                  |                                                                                                                                 |
|------------------|---------------------------------------------------------------------------------------------------------------------------------|
|                  | No Smoking                                                                                                                      |
| P240             | Ground/Bond Container And Receiving Equipment                                                                                   |
| P241             | Use Explosion Proof Electrical/Ventilation/Lighting/Equipment                                                                   |
| P242             | Use Only Non Sparking Tools                                                                                                     |
| P243             | Take Precautionary Measures Against Static Discharge                                                                            |
| P260             | Do Not Breathe Dust/Fume/Gas/Mist/Vapors/Spray                                                                                  |
| P261             | Avoid Breathing Vapors                                                                                                          |
| P264             | Wash Thoroughly After Handling                                                                                                  |
| P270             | Do Not Eat/Drink/Smoke While Using This Product                                                                                 |
| P271             | Use Only Outdoors Or In A Well Ventilated Area                                                                                  |
| P273             | Avoid Release To The Environment                                                                                                |
| P280             | Wear Protective Gloves/Protective Clothing/Eye Protection/Face Protection                                                       |
| P285             | In Case Of Inadequate Ventilation Wear Respiratory Protection                                                                   |
| P301 +P312       | If Swallowed: Call A Poison Center Or Doctor/Physician If You Feel Unwell                                                       |
| P302 + P362+P353 | If On Skin: take Off Contaminated Clothing, Rinse Skin With Water/Shower                                                        |
| P304+P340+P314   | If Inhaled: Remove Person To Fresh Air And Keep Comfortable For Breathing, Get Medical Advice/Attention If You Feel Unwell.     |
| P305+P351+P338   | If In Eyes: Rinse Cautiously With Water For Several Minutes, Remove Contact Lenses If Present And Easy To Do. Continue Rinsing. |
| P308+P313        | If Exposed Or Concerned: Get Medical Advice/Attention                                                                           |
| P330             | Rinse Mouth                                                                                                                     |
| P331             | Do Not Induce Vomiting                                                                                                          |
| P332+P313        | If Skin Irritation Occurs, Get Medical Advice/Attention                                                                         |
| P337+P313        | If Eye Irritation Persists: Get Medical Attention                                                                               |
| P362             | Take Off Contaminated Clothing And Wash Before Reuse                                                                            |
| P370+P378        | In Case Of Fire: Use Carbon Dioxide, Foam, Dry Chemical, Water Fog To Extinguish                                                |
| P391             | Collect Spillage                                                                                                                |
| P403+P235        | Store In A Well Ventilated Place. Keep Cool                                                                                     |
| P405             | Store Locked Up                                                                                                                 |
| P501             | Dispose Of Contents/Container In Accordance With Local/Regional/National/International/Regulations                              |

### III. Composition/Information on Ingredients

| <u>Ingredients:</u>     | <u>CAS #:</u> | <u>CONTENT</u> |
|-------------------------|---------------|----------------|
| Methyl Acetate          | 79-20-9       | 9.5%           |
| Petroleum Hydrocarbons  | 64742-95-6    | 16.38%         |
| Proprietary Ingredients |               | Balance        |

#### California Proposition 65 ingredients

|               |          |       |
|---------------|----------|-------|
| Cumene        | 98-82-8  | 0.39% |
| Ethyl Benzene | 100-41-4 | 0.13% |

#### Section 313 Supplier Notification

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 (40CFR372)

|                        |           |       |
|------------------------|-----------|-------|
| Xylene                 | 1330-20-7 | 0.78% |
| Ethyl Benzene          | 100-41-4  | 0.13% |
| 1,2,4 Trimethylbenzene | 95-63-6   | 8.32% |
| Cumene                 | 98-82-8   | 0.39% |

### IV. First Aid Measures

#### Inhalation

Remove victim from exposure. If difficulty with breathing, administer oxygen and seek medical assistance

#### Eyes

Flush eyes with cold water for a minimum of 15 minutes, lifting lower and upper eye lids throughout. Seek immediate medical attention.

|                  |                                                                                                                                                                                                                    |
|------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <u>Skin</u>      | Immediately remove contaminated clothing. Wash thoroughly with soap and water. If irritation persists seek medical attention. Wash contaminated clothing before reuse.                                             |
| <u>Ingestion</u> | Do not induce vomiting, get immediate medical attention, if vomiting occurs spontaneously keep head below hips to prevent aspiration of liquids into lungs. Do not give anything by mouth to an unconscious person |

## V. Fire Fighting Methods

HMIS Hazard Rating No. 3

Flash Point: 38.3 °C ( 101 °F )

Method: Tag C.C.

General Hazard: Decomposition and combustion products may be toxic.

Auto-Ignition Temp.: 455 °C (MA)

Limits of Flammability

LEL: 3.1% (MA)

UEL: 16.0% (MA)

Extinguishing Media

Carbon dioxide, foam, dry chemical and water fog.

Special Fire & Unusual Hazards

Move containers from area if it can be done without risk. Cool fire-exposed containers with water from the side. As in any fire, wear NIOSH/MSHA approved, pressure demand self contained breathing apparatus and full protective gear.

## VI. Accidental Release Measures

Action To Take For Spills/ Leaks: Avoid contact with skin or eyes. Ventilate area, and eliminate all sources of ignition. Wear appropriate protective gear, contain leak or spill, salvage, clean up residue with absorbent material.

Waste Disposal Method: Handle disposal of waste material in manner that complies with local, state, province and federal regulation. Landfill if solidified, or incineration at agency approved waste-disposal facilities.

## VII. Handling And Storage

Store Dry At 50-95°F. Condition Material To 65-85°F Before Using

Store in a cool dry place. Keep away from heat, open flames or sources of sparks. Keep container closed at all times when not in use.

## VIII. Exposure Controls / Personal Protection

Ventilation: Ventilation is recommended. Air movement must be designed to insure turnover at all locations in work area to avoid build up of heavy vapors.

Personal Protection Equipment: Do NOT wear contact lenses when working with this material. Use chemical goggles/safety glasses with side shields and impervious gloves. Wear clothing with long sleeves and pants. In operations where mists can be generated or the exposure limits may be exceeded, wear a NIOSH/MSHA approved dust/fume respirator selected by a technically qualified person for the specific work conditions. Wear respirator protection whenever airborne concentrations exceed TLV ceilings or TWA, use NIOSH approved respirators for listed hazard.

Confined spaces, room, or tanks are areas where concern for TLV's is especially important. Reference OSHA regulation CFR 29 1910.134 for recommended respiratory protection.



## IX. Physical And Chemical Properties

|                            |                                                     |                                     |                 |
|----------------------------|-----------------------------------------------------|-------------------------------------|-----------------|
| <b>Boiling Point (°C):</b> | <b>N/D</b>                                          | Water/Oil Distribution Coefficient: | N/A             |
| <b>VOC content:</b>        | <b>Pt A &amp; PT B 317g/l<br/>Pt B only 250 g/l</b> | Solubility in Water:                | Negligible      |
| Freezing Point (°C):       | N/A                                                 | <b>Specific Gravity @20° C</b>      | <b>0.94</b>     |
| Vapor Pressure @ 20° C     | 9.5                                                 | pH:                                 | N/A             |
| Vapor Density              | >air                                                | Evaporation Rate:                   | N/A             |
| Odor Threshold:            | N/A                                                 | <b>Odor:</b>                        | <b>Aromatic</b> |
| <b>Appearance:</b>         | <b>Amber liquid</b>                                 |                                     |                 |
| N/A = Not Available        | N/D=NOT Determined                                  | Ca. = Approximate                   |                 |

## X. Stability And Reactivity

HMIS Hazard Rating No. 1

Stability

Stable, avoid contact with moisture.

Incompatibility:

Strong oxidizing agents and reducing agents, strong acids, bases, amines and peroxides..

Hazardous Decomposition Products

Oxides of Carbon; and nitrogen; Decomposition and Combustion products may be toxic.

Conditions To Avoid

Strong acids, bases, amines and peroxides in bulk.

## XI. Toxicity Information

HMIS Hazard Rating No. 1

PRIMARY ROUTE OF ENTRY: Inhalation, dermal, eyes and ingestion.

Effects Of Overexposure

Inhalation:

Vapors can be irritating to nose and mucous membranes.

Eyes:

Contact can cause severe irritation.

Skin Contact:

In some individuals it may cause sensitization.

Ingestion:

Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly leading to death.

Chronic:

This product does not contain chemicals considered to be carcinogenic by NTP, IRAC, ACGIH, OSHA.

## XII. Ecological Information

Marine Pollutant: NL

(NL = Not Listed; P = Moderate; PP = Severe; ND = Not Determined)

## XIII. Disposal Considerations

Handle disposal of waste material in a manner that complies with all applicable local, state, provincial and federal regulations.

## XIV. Transport Information

### DOT SHIPPING INFORMATION

DOT Proper Shipping Name **Flammable liquid, N.O.S (methyl acetate)**  
DOT Hazard Class **3 PG III**  
DOT I.D Number **UN 1993** Label(s) **Flammable**

## XV. Regulatory Information

|                                                       |                                                                                                                                                                                  |
|-------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OSHA Hazard Communication Standard (29 CFR 1910.1200) | Hazardous                                                                                                                                                                        |
| CERCLA/ Super fund (40 CFR 117,302)                   | N/A                                                                                                                                                                              |
| SARA Extremely Hazardous Substances (40 CFR 355)      | N/A                                                                                                                                                                              |
| SARA Hazard Categories (40 CFR 370)                   | Health : Immediate<br>Physical: Delayed                                                                                                                                          |
| SARA Toxic Chemicals (40 CFR 372)<br>Inventory Status | See section 313 advisory in section III<br>The chemicals in this product are listed on the US<br>TSCA Chemical Substance Inventory and the<br>Canadian Domestic Substances List. |

California Proposition 65:

See section III for list of chemicals

## XVI. Other Information

THE INFORMATION HEREIN HAS BEEN COMPILED FROM SOURCES BELIEVED TO BE RELIABLE AND IS ACCURATE TO THE BEST OF OUR KNOWLEDGE. HOWEVER, LymTal INTERNATIONAL INC. CANNOT GIVE ANY GUARANTEES REGARDING INFORMATION FROM OTHER SOURCES, AND EXPRESSLY DOES NOT MAKE ANY WARRANTIES, NOR ASSUMES ANY LIABILITY, FOR ITS USE.

Date of Preparation/ Last Revision: 12/20/2018